

MUST ACCOMPANY THE PRODUCT WHENEVER SHIPPED OR TRANSPORTED IN AN AIRCRAFT HOLD



PRODUCT INFORMATION SHEET

SAFETY DATA SHEET

24 Aug 2026

The products referred to in this document can be defined as 'articles' under regulation (EC) No 1907/2006 (REACH). In light of this, the requirements for a Safety Data Sheet, as set out under article 31 and Annex II of REACH, is not applicable to these products. Accordingly, this Product Information Sheet is provided in the form of a Safety Data Sheet only as a service to our customer and is not based upon any particular requirement of REACH.

1. Product and manufacturer Identification

Alpinestars Commercial Reference: 6991126 - TECH-AIR TYPE IV INFLATOR KIT X1
(hereinafter may also be referred to as Canister Kit)

Manufacturer Information: Alpinestars SpA
Viale Fermi 5, Asolo (TV), 31011,
ITALY Tel: +39 0423 5286

The TECH-AIR TYPE IV INFLATOR KIT X1 is a box 1 high pressure argon and helium gas canister, electrically initiated, type AHS, produced by ARC Automotive Inc., plus a leaflet.

2. Hazard Identification

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

3. Composition and information of the System

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

4. First Aid Measures

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

5. Fire Fighting measures

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

6. Accidental Release Measures

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

7. Handling and Storage

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

8. Exposure Controls and Personal Protection

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

9. Physical and Chemical Properties

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

10. Stability and Reactivity

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

11. Toxicological Information

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

12. Ecological Information

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

13. Disposal Information

Each canister contained in the Canister Kit must not be disposed if the canister itself is still live. For the disposal each canister

must be fired. Fired canisters may be disposed in accordance with national waste regulations or returned to Alpinestars for disposal. Live canisters may be hand carried to an Alpinestars Tech-Air Service Hub for disposal.

14. Transportation Information

UN number: UN3268

UN proper shipping name: SAFETY DEVICES

Transport hazard class (es): 9

Packing group: None

Environmental hazards: None

Special precautions for users:

- By land:
 - Packaging instruction P 902 and LP902
- By sea:
 - Packaging instruction P 902
 - Intervention number: FS supplied by the loader
 - Stowing and separation: category A
- By air:
 - Packaging instruction: 961
 - Code of emergency intervention IDC: 9L
 - Authorized for Commercial flight: maximum 25kg net per parcel
 - Authorized for Cargo flight: maximum 100kg net per parcel

For other information refer to the SDS supplied by ARC Automotive Inc., reported as annex.

15. Regulatory Information

Refer to the SDS supplied by ARC Automotive Inc., reported as annex below.

16. Additional Information

The information contained in this Product Information Sheet relates only to the TECH-AIR TYPE IV INFLATOR KIT X1.

The information is correct to the best of Alpinestars' knowledge at the date of publication. This information is provided only for guidance on the product safe handling, use, processing, storage, transportation and disposal and is not to be considered as a warranty or quality specification.

Refer to the SDS supplied by ARC Automotive Inc. for further information.

ARC Automotive, Inc.

Hybrid Airbag Inflator Assembly

Safety Data Sheet

Version 2.2

Revision Date 06/27/2025

1.) Identification

Product Name: Hybrid Airbag Inflator Assembly

Chemical Name / Synonym / Trade Name:

Pseudonyms/Programs:

Inflator Assembly

AD1, APH, AHS, SH5, CADH, PH7-120, PH7-90, PH5, PH5.1, CH3, CH5, DH7, DH8, D-G2P, S-G2P, G2Ps, SH5B, G3P, SH5.1, SH5.1B, DPH10, SPH10

Manufacturer's Name:

Address:

ARC Automotive, Inc.

1729 Midpark Road Suite 100

Knoxville, TN 37921

ARC Information Phone Number:

Email: (competent person)

(865) 583-7801

regulatory@arcautomotive.com

Emergency Phone (Chemtrec) Inside USA

(ARC, Macedonia-Skopje) Inside EU

(800) 424-9300 (Available outside office hours)

+389(2)271-8390 (Not available outside office hours)

2.) Hazards Identification

Classification according to GHS

Appearance and Odor:

The device is a Steel Cylinder containing pressurized gas and energetic material.

HMIS:

Health:

0

Flammability:

0

Physical Hazard:

2

Personal Protection:

Wear protective clothing/eye protection/Hearing protection

Relevant routes of exposure:

Inhalation:

Skin, Eye, Hearing

None. If device vents/functions, the products of combustion have been demonstrated to comply with ACGIH exposure limits.

Skin contact:

May cause burns if deployed by hand

Eye contact:

Protect eyes from debris

Hearing:

Hearing protection from impact noise, exceeds 85 dBa

Pictogram



Signal Word:

Warning

Hazard statement(s)

H204: Fire or projection hazard

H280: Contains gas under pressure; may explode if heated

Precautionary statement(s)

P280: Wear protective gloves/protective clothing/eye protection

3.) Composition / Information on Ingredients

The article contains a solid pyrotechnic component hermetically sealed within the safety device. Ingredients will not be released under normal conditions of use, or during standard disposal methods. All housing parts of the safety device are interconnected, and the safety device cannot be opened without destroying the whole entity which is the designed use of the approved method of application

Pyrotechnic components represent approximately 20% of the internal volume of this assembly.

4.) First Aid Measures

Inhalation:	None
Skin Contact:	Treat for second degree burn, cool burn area
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention
Hearing:	Avoid repeated exposure

5.) Fire-Fighting Measures

Special Fire and Explosive Hazards:	N/A
Extinguishing Media:	Copious amounts of water
Special Fire Fighting Procedures:	Apply water until the fire is extinguished and the device has cooled to a temperature less than 130°C. The device will relieve pressure at relatively low temperatures and is designed to move no more than 2 to 3 meters when pressure is relieved. No special protective equipment required for firefighters.
Hazardous Combustion Products:	N/A
Conditions Which Cause Ignition:	When the device reaches a temperature in excess of 130 °C, it will release the stored gas. Additional heating will result in burning of the energetic materials. All energetic materials are consumed if the device reaches a temperature in excess of 300°C. If the igniter is stimulated with an electrical current in the excess of 1.2 amps, the device will function; result is rapid

6.) Accidental Release Measures

Environmental precautions:	None expected
-----------------------------------	---------------

- Clean up & Containment Method:** When handled and installed properly, no spills or leaks should occur. If inflator is ruptured and gas generant is present, clean up with non-sparking tools. Avoid spark, static electricity, and open flame. Avoid raising dust. Ventilate area. Wash spill site with water after material pick-up is complete.
- Unusual Fire & Explosion Hazards:** The device (inflator assembly) is a container with compressed gas at up to 7000 psig pressure supplemented by rapidly burning gas generant materials. If the device is exposed to high temperature, the pressure system will release argon/helium gas mixture. Continued heating will cause the propellant to ignite and combustion gases to be released. The combustion gases are non-toxic, and have demonstrated compliance with ACGIH exposure limits.

7.) Handling and Storage

- Handling:** Avoid spark, ESD, impact, friction and open flame. Do not puncture or crush or drop. Post deployment, the surface of the inflator may have trace amounts of particulate and is usually hot. Residue may be irritating to the skin, eyes and mucous membranes.
- Storage:** When not in use, devices should be stored in original shipping containers. Store away from high temperatures, open flame, static electricity, and other ignition sources. Store in accordance with federal, state, and local regulations. Recommend storage at ambient temperatures.

8.) Exposure Controls / Personal Protection

- Engineering Controls:** Do not expose to excessive heat or flame. Do not puncture or crush. Do not expose to electrical current. Do not incinerate.
- Permissive Exposure Limits:** None established
- ACGIH Threshold Limit Values:** None established
- Personal Protective Equipment:** gloves, safety glasses and hearing protection required when deployed for test purposes

9.) Physical and Chemical Properties

Boiling Point:	N/A	Vapor Density:	N/A
Melting Point:	N/A	Specific Gravity:	N/A
Vapor Pressure:	N/A	Evaporation Rate:	N/A
Solubility:	N/A.		

- Appearance and Odor:** The device is a Steel Cylinder/Toroid containing pressurized gas and energetic material.

10.) Stability and Reactivity

- Stability:** Sealed unit is stable when used as designed.

Conditions to Avoid: Sparks, static electricity, open flame, and hot temperatures which can cause functioning of the inflator

Incompatible Materials: None in present form.

11.) Toxicological Information

Relevant routes of exposure: Skin, Eye, Hearing
Inhalation: None. If device vents/functions, the products of combustion have been demonstrated to comply with ACGIH exposure limits.
Skin contact: May cause burns if deployed by hand
Eye contact: Protect eyes from debris
Hearing: Hearing protection from impact noise, exceeds 85 dBa

Carcinogen Status: None Known

Target Organ and Other Health Effects: None Known

12.) Ecological Information

When used properly, no environmental effects are anticipated.

Persistence and Degradability

Perchlorate Material – Special handling may apply. See www.dtsc.ca.gov/hazardouswaste/perchlorate

13.) Disposal Considerations

Information provided is for unused product only

Recommended method of disposal: Dispose in accordance with Federal, State and local regulations

EPA hazardous waste number: Not a RCRA Waste

14.) Transportation Information

SPECIAL HANDLING, STORAGE, AND PACKAGING RECOMMENDATIONS: This SDS is not intended to have all required shipping information. When not used, devices should be stored in original shipping containers. Do not drop or expose to temperatures above 107C.

Identification number	UN3268
Proper shipping name	Safety Device
Hazard Classification	Class 9
Special Permit	Product Dependent. Available upon request For
further information contact:	ARC Automotive, Inc
	1729 Midpark Rd.
	Knoxville, TN 37921

Safety devices associated with this document are in compliance with 49 CFR §173.166.

15.) Regulatory Information

United States Regulatory Information

TSCA 8 (b) Inventory Status:	Contains none listed
TSCA 12 (b) Export Notification:	None
CERCLAS/Sara	None Listed
California Proposition 65:	Could affect California's Perchlorate Contamination Prevention Act 2003 (AB 826)

European Regulatory Information

REACH:	1907/2006 EC Annex II, amended 2015/830/EU (EU REACH)
CLP:	1272/2008/EC (EU CLP)

The Act on Registration and Evaluation, etc. of Chemicals (K-REACH)

16.) Other Information

Date prepared: June 27, 2025 KDW

DISCLAIMER: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices or from any hazards inherent in the nature of the product.