

# KATANA

## HIGH TORQUE

100% SYNTHÉTIQUE



**SPORT**

**API SP / JASO MA2**



Available viscosity grades :

**15W-50 / 15W-60 / 20W-50**

KATANA HIGH TORQUE is a 100% synthetic 4-stroke motorcycle engine oil made of high-quality polyalphaolefins (PAOs), esters and additives. Designed to provide optimum protection at high temperatures and under very heavy loads, it is dedicated to high-capacity, high-torque engines. Ideal for cruisers, it promotes a smooth, high-performance driving experience.

PACKING UNITS :



TECHNICAL DATA :

| TEST                  | MÉTHOD                  | TYPICAL VALUES |        |        | MEASURE UNITS      |
|-----------------------|-------------------------|----------------|--------|--------|--------------------|
|                       |                         | 15W-50         | 15W-60 | 20W-50 |                    |
| Density at 20°C       | ASTM D4052              | 0,871          | 0,876  | 0,871  | g/cm <sup>3</sup>  |
| Viscosity at 40°C     | ASTL D445 or ASTM D7279 | 125,5          | 152    | 130,1  | Mm <sup>2</sup> /s |
| Viscosity at 100°C    | ASTL D445 or ASTM D7279 | 19             | 23,6   | 19,44  | Mm <sup>2</sup> /s |
| Viscosity Index (VIE) | ASTM D2270              | 172            | 187    | 171    | -                  |
| Pour point            | ASTM D97                | -42            | -42    | -39    | °C                 |
| Flash point           | ASTM D92                | 260            | 242    | 271    | °C                 |
| TBN                   | ASTM D2896              | 7,08           | 7,08   | 7,08   | mg KOH/g           |